


## Steel CSK-120° Standard Rivets

Standard rivets are used in numerous applications to secure two or more components together. Typically used in sheet type products, the Standard rivet is easily installed with access only required from one side of the assembly.

STO .



eel F eel

Finish: Body: Zinc Plated Mandrel: Zinc Plated



Diameter (A) mm	Part Code	Grip Range (Min ~ Max) mm	Hole Size (Nominal) mm	B mm	C mm	D	E	Shear (Min) kN	Tensile (Min) kN	Pack Size Pcs	
Standard											
<b>4.80</b> (3/16)	72SS-0602	1.60 ~ 3.20	4.90	8.00	8.90	1.90	2.70	2.40	3.02	500	
MultiGrip											
<b>3.20</b> (1/8)	72SSMG-0403	1.00 ~ 4.80	3.30	9.90	6.40	1.30	2.05	1.10	1.40	1,000	
<b>4.00</b> (5/32)	72SSMG-0504	1.60 ~ 6.40	4.10	11.4	6.80	1.60	2.65	1.80	2.10	1,000	
<b>4.80</b> (3/16)	72SSMG-0604 72SSMG-0606 72SSMG-0608 72SSMG-0610	1.60 ~ 6.40 4.80 ~ 9.60 8.00 ~ 12.7 12.7 ~ 17.5	4.90	12.7 15.9 19.3 23.8	8.90	1.90	2.70	2.60	3.10	500 500 500 500	

All diagrams and drawings are intended for illustration and measurement purposes only. Dimensions and specifications may change without prior notice. Please refer to your distributor for the most up-todate data sheet. The test data presented offers approximate average strength values based on multiple tests conducted in various materials and thicknesses. For applications requiring precise strength figures or when the applied load approaches the published values, we strongly recommend conducting tests specific to your use case. **REVISED MAY 2025** 

Auckland 09 276 7021 | Christchurch 03 341 3320 | Free Phone 0800 748 832 | info@rivtec.co.nz | www.rivtec.co.nz