

## Aluminium Large Flange Standard Rivets

Standard rivets are used in numerous applications to secure two or more components together. Typically used in sheet type products, the Standard rivet is easily installed with access only required from one side of the assembly.

**Material:** Body: Aluminium  
Mandrel: Carbon Steel

**Finish:** Body: Plain Finish  
Mandrel: Zinc Plated



Diameter mm	Part Code	Grip Range mm	Hole Size (nom) mm	A mm	B mm	C mm	D mm	E mm	Shear (min) KN	Tensile (min) KN	Box Qty pcs
3.2	73ASL-0402	1.00 - 3.20	3.30	3.20	7.00	9.60	1.40	1.90	0.76	0.98	1000
	73ASL-0403	3.20 - 4.80	3.30	3.20	8.20	9.60	1.40	1.90	0.76	0.98	1000
	73ASL-0404	4.80 - 6.40	3.30	3.20	9.90	9.60	1.40	1.90	0.76	0.98	1000
	73ASL-0406	7.90 - 9.50	3.30	3.20	13.0	9.60	1.40	1.90	0.76	0.98	1000
	73ASL-0408	9.50 - 12.7	3.30	3.20	16.2	9.60	1.40	1.90	0.76	0.98	1000
4.0	73ASL-0504	4.80 - 6.40	4.10	4.00	10.5	12.0	1.90	2.40	1.16	1.56	500
	73ASL-0505	6.40 - 7.90	4.10	4.00	12.0	12.0	1.90	2.40	1.16	1.56	500
	73ASL-0506	7.90 - 9.50	4.10	4.00	13.6	12.0	1.90	2.40	1.16	1.56	500
4.8	73ASL-0604	4.80 - 6.40	4.90	4.80	11.1	16.0	2.40	2.90	1.70	2.23	500
	73ASL-0605	6.40 - 7.90	4.90	4.80	12.7	16.0	2.40	2.90	1.70	2.23	250
	73ASL-0606	7.90 - 9.50	4.90	4.80	14.3	16.0	2.40	2.90	1.70	2.23	250
	73ASL-0608	9.50 - 12.7	4.90	4.80	17.5	16.0	2.40	2.90	1.70	2.23	250
	73ASL-0610	12.7 - 15.9	4.90	4.80	20.7	16.0	2.40	2.90	1.70	2.23	250
	73ASL-0612	15.9 - 19.0	4.90	4.80	23.8	16.0	2.40	2.90	1.70	2.23	250
	73ASL-0614	19.0 - 22.2	4.90	4.80	27.0	16.0	2.40	2.90	1.70	2.23	250
	73ASL-0616	22.2 - 25.4	4.90	4.80	30.2	16.0	2.40	2.90	1.70	2.23	200
	73ASL-0620	25.4 - 31.8	4.90	4.80	36.5	16.0	2.40	2.90	1.70	2.23	150
	73ASL-0622	31.8 - 34.9	4.90	4.80	40.0	16.0	2.40	2.90	1.70	2.23	150

Dimensions and specifications are subject to change without notice. Check your distributor for the latest data sheet. The test data provides approximate strength values averaged in multiple tests in various materials and thicknesses. We recommend testing your application when an exact strength figure is required, or the load to be applied comes close to the published data.  
Revised July 2023