

Standard Rivets | 73SS

All Steel | Dome HD

Standard rivets are used in numerous applications to secure two or more components together. Typically used in sheet type products, the Standard rivet is easily installed with access only required from one side of the assembly.

Material: Body: Steel
Mandrel: Steel



Diameter	Part Code	Grip	Hole	A	B	C	D	E	Shear	Tensile	Box Qty
mm		mm	mm	mm	mm	mm	mm	mm	KN	KN	pcs
3.2	73SS-0401	0.00 - 1.60	3.30	3.20	5.10	6.20	1.00	1.40	1.16	1.38	1000
	73SS-0402	1.60 - 3.20	3.30	3.20	6.70	6.20	1.00	1.40	1.16	1.38	1000
	73SS-0403	3.20 - 4.80	3.30	3.20	8.20	6.20	1.00	1.40	1.16	1.38	1000
	73SS-0404	4.80 - 6.40	3.30	3.20	9.90	6.20	1.00	1.40	1.16	1.38	1000
	73SS-0405	6.40 - 7.90	3.30	3.20	11.1	6.20	1.00	1.40	1.16	1.38	1000
	73SS-0406	7.90 - 9.50	3.30	3.20	13.0	6.20	1.00	1.40	1.16	1.38	1000
	73SS-0408	9.50 - 12.7	3.30	3.20	16.2	6.20	1.00	1.40	1.16	1.38	1000
4.0	73SS-0502	1.60 - 3.20	4.10	4.00	7.30	7.60	1.20	2.40	1.65	2.10	1000
	73SS-0503	3.20 - 4.80	4.10	4.00	8.90	7.60	1.20	2.40	1.65	2.10	1000
	73SS-0504	4.80 - 6.40	4.10	4.00	10.5	7.60	1.20	2.40	1.65	2.10	1000
	73SS-0505	6.40 - 7.90	4.10	4.00	11.9	7.60	1.20	2.40	1.65	2.10	1000
	73SS-0506	7.90 - 9.50	4.10	4.00	13.5	7.60	1.20	2.40	1.65	2.10	500
	73SS-0508	9.50 - 12.7	4.10	4.00	16.8	7.60	1.20	2.40	1.65	2.10	500
4.8	73SS-0602	1.60 - 3.20	4.90	4.80	8.00	9.20	1.60	2.80	2.40	3.03	500
	73SS-0603	3.20 - 4.80	4.90	4.80	9.50	9.20	1.60	2.80	2.40	3.03	500
	73SS-0604	4.80 - 6.40	4.90	4.80	11.1	9.20	1.60	2.80	2.40	3.03	500
	73SS-0605	6.40 - 7.90	4.90	4.80	12.7	9.20	1.60	2.80	2.40	3.03	500
	73SS-0606	7.90 - 9.50	4.90	4.80	14.3	9.20	1.60	2.80	2.40	3.03	500
	73SS-0608	9.50 - 12.7	4.90	4.80	17.5	9.20	1.60	2.80	2.40	3.03	500
	73SS-0610	12.7 - 15.9	4.90	4.80	20.9	9.20	1.60	2.80	2.40	3.03	500
	73SS-0612	15.9 - 19.0	4.90	4.80	23.8	9.20	1.60	2.80	2.40	3.03	250
	73SS-0616	22.2 - 25.4	4.90	4.80	30.6	9.20	1.60	2.80	2.40	3.03	250
6.4	73SS-0802	1.60 - 3.20	6.50	6.40	8.00	12.2	2.10	3.70	4.45	5.52	250
	73SS-0804	4.80 - 6.40	6.50	6.40	12.4	12.2	2.10	3.70	4.45	5.52	250
	73SS-0806	6.40 - 9.50	6.50	6.40	15.5	12.2	2.10	3.70	4.45	5.52	250
	73SS-0808	9.50 - 12.7	6.50	6.40	18.7	12.2	2.10	3.70	4.45	5.52	250
	73SS-0810	13.0 - 17.0	6.50	6.40	22.2	12.2	2.10	3.70	4.45	5.52	250

Dimensions and specifications are subject to change without notice. Check your distributor for the latest data sheet. The test data provides approximate strength values averaged in multiple tests in various materials and thicknesses. We recommend testing your application when an exact strength figure is required, or the load to be applied comes close to the published data.