

Steel Large Flange Standard Rivets

Standard rivets are used in numerous applications to secure two or more components together. Typically used in sheet type products, the Standard rivet is easily installed with access only required from one side of the assembly.

Material: Body: Carbon Steel Finish: Body: Zinc Plated

Mandrel: Carbon Steel Mandrel: Zinc Plated





Diameter (A) mm	Part Code	Grip Range (Min ~ Max) mm	Hole Size (Nominal) mm	B	C mm	D mm	E	Shear (Min) kN	Tensile (Min) kN	Pack Size Pcs
Multigrip										
4.80 (3/16)	73SSL-0606XG	1.00 ~ 9.00	4.90	14.0	16.0	1.60	2.80	2.40	3.03	100
Standard Grip										
4.80 (3/16)	73SSL-0608 73SSL-0610 73SSL-0612 73SSL-0616	9.50 ~ 12.7 12.7 ~ 15.9 15.9 ~ 19.0 22.2 ~ 25.4	4.90	17.9 20.7 23.5 30.6	16.0	1.60	2.80	2.40	3.03	250 250 250 150

All diagrams and drawings are intended for illustration and measurement purposes only. Dimensions and specifications may change without prior notice. Please refer to your distributor for the most up-to-date data sheet. The test data presented offers approximate average strength values based on multiple tests conducted in various materials and thicknesses. For applications requiring precise strength figures or when the applied load approaches the published values, we strongly recommend conducting tests specific to your use case.

REVISED MAY 2025