

Stainless Dome Head Sealed Rivets

The closed end rivet produces a seal that prevents the passage of liquid or vapor at pressures up to 100 psi. The seal is possible thanks to a unique cup-shaped design and configuration that prevents vapor or liquid from getting around or through the set rivet.

304 Stainless Steel Finish: Body: Polished Mandrel: Polished Mandrel: 304 Stainless Steel





Diameter (A) mm	Part Code	Grip Range (Min ~ Max) mm	Hole Size (Nominal) mm	B	C	D mm	E	Shear (Min) kN	Tensile (Min) kN	Pack Size Pcs
3.20 (1/8)	73TST-0402 73TST-0403 73TST-0404	1.50 ~ 3.20 2.50 ~ 4.50 4.80 ~ 6.40	3.30	8.30 10.0 12.3	6.20	1.00	1.80	1.78	2.00	1,000 1,000 1,000
4.80 (3/16)	73TST-0604 73TST-0606 73TST-0608 73TST-0610	4.80 ~ 6.40 6.40 ~ 9.50 9.50 ~ 12.7 12.7 ~ 15.9	4.90	13.5 16.9 19.8 22.2	9.20	1.60	2.80	3.79	4.00	500 500 500 250

All diagrams and drawings are intended for illustration and measurement purposes only. Dimensions and specifications may change without prior notice. Please refer to your distributor for the most up-to-date data sheet. The test data presented offers approximate average strength values based on multiple tests conducted in various materials and thicknesses. For applications requiring precise strength figures or when the applied load approaches the published values, we strongly recommend conducting tests specific to your use case.

REVISED MAY 2025