


## Aluminium Large Flange Closed End

The Large Flange head of the Closed End IN78 Series is optimal for high push-out applications. Designed for installation into metric holes, key features include a Tapered body for easy insertion and Splined body to improve torque-to-turn resistance. Ideal for applications where sealing to prevent the ingress of solids or moisture is desirable.



## Material: Aluminium



Thread Size (Pitch)	Part Code	<b>Grip Range</b> (Min ~ Max) <b>mm</b>	Hole Size	A mm	B	C mm	D	Pull-Out (Min) kN	Push-Out (Min) kN	Torque (Max) Nm
<b>M5</b> x 0.80	IN78-0530-CE	0.50 ~ 3.00	7.00	6.90	18.0	10.0	1.20	5.90	1.50	5.00
<b>M6</b> x 1.00	IN78-0623-CE IN78-0640-CE	0.50 ~ 2.30 2.30 ~ 4.00	9.00	8.90	20.5 22.0	12.0	1.50	8.60	2.90	8.00

All diagrams and drawings are intended for illustration and measurement purposes only. Dimensions and specifications may change without prior notice. Please refer to your distributor for the most up-todate data sheet. The test data presented offers approximate average strength values based on multiple tests conducted in various materials and thicknesses. For applications requiring precise strength figures or when the applied load approaches the published values, we strongly recommend conducting tests specific to your use case. **REVISED MARCH 2025**